



E360 9.0K After Market

Printer: E360

Declaration of Yield: Average Cartridge Yield 9000 standard pages Declared yield value in accordance with ISO/IEC 19752

Average 9543
Std Dev 394
90% Lower Confidence 9299

For questions concerning testing contact: Lexmark International Inc. 740 West New Circle Rd. Lexington, Ky. 40550 USA Attn: Laser Supplies Product Manager

Date tested start 10-Jun-2008 stop 13-Jun-2008

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake 2nd shake
Print mode Continuous
Number of printers tested 3
Media used Tidal Hammermill - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version Long Bow Lexmark G9
Operating system Windows XP SP2
Application software Acrobat version 7.0.0
Test page version 19752\_Test\_Chart\_Ver200406.pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity (Avg, Max, Min), Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAS08152149E, CAS08133301C, etc.

Comments and or exceptions: